

SAFETY DATA SHEET

102 – Primer Surfacer Hardener

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

| | |
|--|---|
| Product Name | : 102 – Primer Surfacer Hardener |
| Intended Use | : Use in coatings - Hardener |
| Manufacturer Legal Name | : BK ENTERPRISES |
| Manufacturer Trade Name | : NEON COATINGS |
| Registered Office Address | : Plot No 145, BK Enterprises, Koorgally Industrial Area Phase 3 Mysuru (Mysore), Karnataka, 570018 INDIA |
| Telephone No | +91 8550855014 |
| Email | customerservice@flurolac.com |
| Supplier Emergency Telephone No | +91 8550855014 |

SECTION 2: HAZARDS IDENTIFICATION

| | |
|---|---|
| Product Definition | : Mixture |
| <u>GHS Classification:</u> | |
| Flammable Liquid | : Category 3 |
| Acute Toxicity | Oral Category 5 Dermal Category 5 Inhalation Category 4 |
| Skin corrosion/ irritation | : Category 2 |
| Serious eye damage/ eye irritation | : Category 2A |
| Carcinogenicity | : Category 2 |
| Aquatic toxicity (Acute) | : Category 3 |

SAFETY DATA SHEET

102 – Primer Surfacer Hardener

Label elements

Hazard pictograms



Signal word : Warning

Hazard statements : Flammable liquid and vapour.
Harmful if inhaled
May cause an allergic skin reaction.
May cause respiratory irritation.

Precautionary statements

Prevention : Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Avoid release to the environment. Do not breathe vapour or spray.

Response : IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Mixtures : Mixture

Hazardous components

| <u>Chemical Name</u> | <u>CAS No.</u> | <u>Concentration %</u> |
|-----------------------------|-----------------------|-------------------------------|
| Xylene | 1330-20-7 | ≥05 - ≤10 |
| n-Butyl Acetate | 23-86-4 | ≥10 - ≤20 |
| Methoxy Propyl Acetate | 108-65-6 | ≥05 - ≤10 |
| Solvent Naphta (Petroleum) | 64742-95-6 | ≥05 - ≤10 |
| Aliphatic polyisocyanate. | 8182-81-2 | ≥40 - ≤60 |

SECTION 4: FIRST-AID MEASURES

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- If Swallowed** : Immediately call a POISON CENTER or doctor/physician

SECTION 5: FIRE-FIGHTING MEASURES

- Unsuitable extinguishing media** : Do not use water jet
- Suitable Recommended extinguishing media** : Alcohol-resistant foam, CO₂, powders, water spray, dry Sand.
- Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
Carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.
- Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
- Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Avoid all sources of ignition (e.g. naked lights, unprotected light bulbs, electric hand tools).

Ventilate the area and avoid breathing vapors.

Wear protective clothing and self-contained breathing apparatus when dealing with spillage or fire.

Collect spillage, where practicable, for safe disposal.

Should be disposed of wastes and empty containers in accordance with regulations made under the control of pollution acts and the environmental protection acts.

Collect spillage, where practicable, using absorbent material, and dispose of spillage on the floor in a safe manner.

Keep away from drains, surface-and ground-water and soil.

Do not allow spills to enter drains or water courses.

SECTION 7: HANDLING AND STORAGE

Store in a well-ventilated place.

Keep container tightly closed. Store locked up.

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Storage temperature : Store bellow 40 deg.C. (104deg.F.)

SAFETY DATA SHEET

102 – Primer Surfacer Hardener

SECTION 8: EXPOSURE CONTROL / PERSONAL PROTECTION

Exposure limit:

| Ingredient Name | Occupational exposure limits |
|-------------------------------|--|
| Xylene | TWA: 221 mg/m ³ , 0 times per shift, 8 hours. |
| | TWA: 50 ppm, 0 times per shift, 8 hours. |
| | STEL: 442 mg/m ³ , 0 times per shift, 15 minutes. |
| | STEL: 100 ppm, 0 times per shift, 15 minutes. |
| n-Butyl Acetate | STEL: 150 ppm 15 minutes |
| | TWA: 50 ppm 8 hours |
| Methoxy Propyl Acetate | TWA: 275 mg/m ³ 8 hours. |
| | TWA: 50 ppm 8 hours. |
| | STEL: 550 mg/m ³ 15 minutes. |
| | STEL: 100 ppm 15 minutes. |

Personal protection :

Respiratory protection : Wear NIOSH-Approved appropriate equipment.

Hand protection : Wear impervious gloves.

Eye protection : Wear chemical splash goggles and face shield when eye and face contact is possible due to splashing or spraying of material.

Skin protection : Wear chemical resistant clothing such as gloves, apron, boots or whole bodysuits made from neoprene, as appropriate.

Environmental exposure control : Do NOT let this product enter the environment

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Clear liquid
Color : Colorless
Odor : Solvent odor
pH : Not available.
Melting point/freezing point : Not available.
Initial boiling point and boiling range : >100°C
Flash point : Closed cup: 26°C
Evaporation rate : Not available.
Relative density : 1.04
Solubility in water : none or poor in water

SAFETY DATA SHEET

102 – Primer Surfacer Hardener

SECTION 10: STABILITY AND REACTIVITY

- Stability** : Stable under recommended storage and handling conditions (see section 7).
When exposed to high temperature, may produce hazardous decomposition products such as carbon monoxide, carbon dioxide, oxides of nitrogen and smoke.
- Hazardous reaction** : Hazardous reaction will not occur.
- Condition to avoid** : Avoid heating temperatures above 30 deg.C.
- Materials to avoid** : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid possible exothermic reactions
- Hazardous decomposition products** : The products decomposed on heating producing their oxide or monomers.

SECTION 11: TOXICOLOGICAL INFORMATION

There are no data available on the product itself.

Toxicological information of ingredients

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|------------------------------------|---------------------------------|---------|--------------|----------|
| xylene | LC50 Inhalation Vapour | Rat | 27.6 mg/l | 4 hours |
| | LD50 Dermal | Rabbit | >2000 mg/kg | - |
| | LD50 Oral | Rat | >2000 mg/kg | - |
| n-butyl acetate | LC50 Inhalation Vapour | Rat | >21.1 mg/l | 4 hours |
| | LD50 Dermal | Rabbit | >14112 mg/kg | - |
| | LD50 Oral | Rat | 10760 mg/kg | - |
| Methoxy Propyl Acetate | LD50 Dermal | Rat | >5000 mg/kg | - |
| | LD50 Oral | Rat | >5000 mg/kg | - |
| Solvent Naphta (Petroleum) | LC50 Inhalation Vapour | Rat | >6193 mg/l | 4 hours |
| | LD50 Dermal | Rabbit | >3160 mg/kg | - |
| | LD50 Oral | Rat | 3592 mg/kg | - |
| Aliphatic polyisocyanate | LC50 Inhalation Dusts and mists | Rat | 2.18 mg/l | 4 hours |
| | LD50 Dermal | Rabbit | >2000 mg/kg | - |
| | LD50 Dermal | Rat | >2000 mg/kg | - |

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

There are no data available on the mixture itself

Do not allow to enter drains or watercourses.

| Product/ingredient name | Result | Species | Exposure |
|--|-------------------------|-----------|----------|
| xylene | Acute EC50 1 to 10 mg/l | Algae | 72 hours |
| | Acute EC50 1 to 10 mg/l | Crustacea | 48 hours |
| | Acute LC50 1 to 10 mg/l | Fish | 96 hours |
| n-butyl acetate | Acute EC50 397 mg/l | Algae | 72 hours |
| | Acute EC50 44 mg/l | Crustacea | 48 hours |
| | Acute LC50 18 mg/l | Fish | 96 hours |
| Methoxy Propyl Acetate | Acute EC50 >1000 mg/l | Algae | 96 hours |
| | Acute EC50 408 mg/l | Crustacea | 48 hours |
| | Acute LC50 134 mg/l | Fish | 96 hours |
| Solvent Naphta (Petroleum) | Acute EC50 2.9 mg/l | Algae | 72 hours |
| | Acute EC50 3.2 mg/l | Crustacea | 48 hours |
| | Acute LC50 9.2 mg/l | Fish | 96 hours |
| Aliphatic polyisocyanate | Acute EC50 >1000 mg/l | Algae | 72 hours |
| | Acute EC50 >100 mg/l | Crustacea | 48 hours |
| | Acute LC50 >100 mg/l | Fish | 96 hours |

SECTION 13: DISPOSAL CONSIDERATIONS





Avoid release to the environment

Dispose of contents/container in accordance with local/regional/national/ international regulation.

SAFETY DATA SHEET

102 – Primer Surfacer Hardener

SECTION 14: TRANSPORT INFORMATION

| | ADR/RID | AND | IMDG | IATA |
|-----------------------------------|--|--|--|--|
| UN number | UN1263 | UN1263 | UN1263 | UN1263 |
| UN proper shipping name | PAINT RELATED MATERIAL | PAINT RELATED MATERIAL | PAINT RELATED MATERIAL | PAINT RELATED MATERIAL |
| Transport hazard class(es) | 3  | 3  | 3  | 3  |
| Packing group | III | III | III | III |

Special precautions for users: always transport in closed containers that are upright and secure

SECTION 15: REGULATORY INFORMATION

Please refer to any other national measures that may be relevant.

SECTION 16: OTHER INFORMATION

The data are based on the current state of our knowledge, and are intended to describe the product with regard to the requirements of safety. The data should not be taken to imply any guarantee of a particular or general specification. It is the responsibility of the user of the product to ensure to his satisfaction that the product is suitable for the intended purpose and method of use. We do not accept responsibility for any harm caused by the use of this information.